



BIAXIAL GEOGRIDS or ECOVOID™ HD LAYER

TECHNICAL NOTE

This technical note deals with the use of a Biaxial Geogrid or Ecovoid™ HD layer above EcoRain Tank structures.

EcoRain Tank Systems recommends the use of one-layer Biaxial Geogrid 12 inches below sub-grade in vehicular traffic applications with two to four feet cover. A second layer of Biaxial Geogrid may be used when cover exceeds four feet.

This recommendation is based on increasing the safety factor due to possible lack of compaction during backfill - the Geogrid will create a "bridge" in weak soil areas.

Overlap the Geogrid at least 3 feet beyond the perimeter of the EcoRain Tank structure. Place 2 inches of gravel under and over the Geogrid - this will secure the Geogrid in place with the required tension for proper functioning. Pin the Geogrid to the undisturbed side walls.

Alternately, a layer of EcoRain 1" or Ecovoid™ HD 2" Cells can be used instead of the Biaxial Geogrid to provide more strength and disbursement of load. A layer of filled Ecovoid™ HD 2" Drainage Cells withstands 6,030 psi loading. Install as above.

While EcoRain Tank Systems recommends the use of Biaxial Geogrid or Ecovoid™ HD Cells in vehicular traffic applications like parking lots, it is the Engineer's decision to specify its use. Installers must follow the Engineer's specification.

DISCLAIMER: All information provided in this publication is correct to the best of the Company's knowledge and is given out in Good Faith. This information is intended only as a general guide, no responsibility can be accepted for any errors, omissions, or incorrect assumption. As each project is unique, and as EcoRain Tank Systems and Its distributors and agents worldwide have no direct control over the methods employed by the user in specifying, installing, or supervising its products. No responsibility is accepted by EcoRain Tank Systems and/or its distributors and agents worldwide. Users should satisfy themselves as to the suitability of the product for their purpose.