

ECOVOID™ HD 2" (50mm) SPECIFICATION SHEET

HEAVY DUTY



ET-1401

	Standard Used	Metric	Imperial
Width		300mm	11.75" / 0.98'
Length		500mm	19.4" / 1.62'
Height		50mm	2.0" / 0.17'
Area		0.150 m ²	1.59 ft ²
Void Storage Area		87.6% - 6.8 mm ³	87.6% - .24 ft ³
Material	ASTM D4104	100% Recycled Polypropylene	
Biological & Chemical Resistance		Material is unaffected by mould, algae, soil-borne chemicals, bacteria & bitumen.	
Service Temperature		-30°C to 120°C	-22°F to 248°F
Unconfined Compressive Strength	ASTM D1621	±283.90 t/m ²	±405.3 psi
Flow Rate per Unit Width	ASTM D4716	>212 lt/min	>56.00 gal/min

Compressive Strength Test Filled with Sand - Products must have a maximum deformation of <25%.

Filled with Sand	Area (mm ²)	Area (inches ²)	Load (Kg)	Load (lbs)	Compressive Strength (t/m ²)	Compressive Strength (psi)
	54,554.73	84.56	231,332.1	510,000	±5,201.01	±7,395

NOTE: ALL ECORAIN TANK PRODUCTS & SYSTEMS ARE WORLDWIDE PATENT PENDING & DESIGN REGISTERED

Disclaimer: All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. This information is intended only as a general guide, no responsibility can be accepted for any errors, omissions, or incorrect assumption. As each project is unique, and as EcoRain Tank Systems and its distributors and agents worldwide have no direct control over the methods employed by the user in specifying, installing, or supervising of its products hence EcoRain Tank Systems and its distributors and agents worldwide accept no responsibility. Users should satisfy themselves as to the suitability of the product for their purpose. All product designs and specification are subject to change without further notice.



EcoRain Tank Systems of America, Inc.

contact@ecoraintank.com

+1.818.501.0424

www.ecoraintank.com